

TURRET NETWORK CAMERA

T3Z2812IP5MP-AI



5MP HIGH DEFINITION | MOTORIZED 2.8MM LENS | POE (POWER OVER ETHERNET)

4 PCS LED (45M IR) | 120DB-WDR | IP66

ANALYTIC ENABLED | H.265 & H.264 CODEC | 3 YEARS WARRANTY



FULL HD
5MPLENS
2.8MM

IR 45M

EMBEDDED
MICRO

IP66

POE

3
YEARS
WARRANTY

TURRET NETWORK CAMERA

TECHNICAL SHEET

T3Z2812IP5MP-AI

RESOLUTION	5MP 2592(H)×1944(V)
IMAGE SENSOR	1/2.7" PROGRESSIVE CMOS
MIN. ILLUMINATION	COLOR 0.01LUX @ F1.2(AGC ON) ; B/W 0 LUX @ IR ON
SHUTTER	1/5 ~ 1/20000S
SLOW SHUTTER	SUPPORT
LENS	2.8 ~ 12MM (MOTORIZED) H.FOV: 102 ~ 31°
F NO.	F NO. 1.83 (W) ~ 3.32(T)±5%
DAY & NIGHT	IR CUT FILTER WITH AUTO SWITCH (DAY/NIGHT/AUTO/SCHEDULE)
DIGITAL NOISE REDUC.	3D DNR
WDR	120 DB
VIDEO COMPRESSION	H.265/H.264
VIDEO BIT RATE	8KBPS ~ 8MBPS
TRIPLE STREAM	YES
RESOLUTION	MAINSTREAM (1~20FPS DEFAULT 20FPS) 5MP (2592X1944), 4MP (2592X1520), 3MP (2304X1296) (2048X1535) 1080P (1920X1080), 720P (1280X720), SUBSTREAM 720P (1280X720), VGA (640X480), QVGA (320X240) MOBILESTREAM VGA (640X480), QVGA (320X240)
IMAGE SETTINGS	FLIP, ROTATION, CORRIDOR MODE, SATURATION, BRIGHTNESS, CONTRAST, HUE, SHARPNESS ADJUSTABLE
BLC	SUPPORT
ROI	SUPPORT
PRIVACY MASK	SUPPORT
SMART FEATURE	FACE DETECTION, HUMAN/VEHICLE DETECTION, PID, LCD, SOD, CC

PROTOCOLS	TCP/IP, HTTP, DHCP, DNS, DDNS, RTP/RTSP, PPPOE, SMTP, NTP, UPNP, SNMP, HTTPS, FTP
SYSTEM COMPATIBILITY	ONVIF (PROFILE S, PROFILE G, PROFILE T)
INTERFACE	RJ45 10M / 100M ETHERNET INTERFACE X1
LED	4 PCS (ARRAY)
IR RANGE	UP TO 45 M
SD STORAGE	YES (MICRO SD/SDHC/SDXC SLOT, UP TO 128 GB)
ALARM TRIGGER	1 INPUT / 1 OUTPUT
AUDIO	1 INPUT / 1 OUTPUT (RCA)
VIDEO OUTPUT	NA
RESET BUTTON	YES
POE	YES
WATER PROOF	IP 66
POWER SUPPLY	DC 12V/POE
CONSUMPTION	≤ 7.9W
DIMENSION	Ø135.56X127.04MM
WEIGHT	APPR. 881G
STORAGE TEMP	-30~+60°C/LESS THAN ≤ 95% RH
OPERATING TEMP	-30~+55°C

